

# Vapour2™ PRO SERIES 3X

## The Anatomy of Your Device

- 1. Cartridge Chamber:** Magnetically secures your cartridge
- 2. LED Light:** Indicates the activation status of Series 3X
- 3. Activation Button:** Controls vapor production
- 4. Manual Control LED Lights:** Indicates selected voltage or temperature
- 5. LED Perimeter:** Glows different colors to indicate the temperature & remaining charge of Series 3X
- 6. Metal Charge Port:** Connects to the magnetic head of the USB charging cord

## The Anatomy of a Series 3X Cartridge

- A. Replaceable Mouthpiece:** Available in gunmetal, silver, angled, and classic.
- B. Air Intake Ring:** Adjust to change airflow
- C. Replaceable Ceramic Atomizer:** Available in 0.9 Ω, 1.2 Ω & 1.5 Ω

## Your 2-in-1 Vaporizer

Series 3X is capable of vaporizing two mediums: e-liquid and loose leaf. Your Series 3X Kit comes with one Series 3X E-liquid cartridge, three interchangeable ceramic atomizers (0.9 Ω, 1.2 Ω, and 1.5 Ω), and one Series 3 PG Ceramic E-liquid cartridge. Loose Leaf cartridges may be purchased separately.

## Package Contains:

- 1 S3X Vaporizer
- 1 S3X E-Liquid Cartridge w/ replaceable atomizers:
- 1 0.9 Ohm Ceramic Atomizer
- 1 1.2 Ohm Ceramic Atomizer
- 1 1.5 Ohm Ceramic Atomizer
- 1 S3X Gunmetal E-liquid Cartridge Mouthpiece
- 1 S3 PG Ceramic E-Liquid Cartridge
- 1 USB Charger
- 1 User Manual



MANUAL  
TEMPERATURE  
CONTROL



SUB-OHM  
CAPABLE



VARIABLE  
AIRFLOW



LARGER  
CAPACITY  
BATTERY



BATTERY  
LIFE  
INDICATOR



MAGNETIC  
CARTRIDGES  
& CHARGER

## COMPATIBLE CARTRIDGES

### SERIES 3X



S3X E-LIQUID

### SERIES B®



S3 PG Ceramic E-Liquid

S3 VG Ceramic E-Liquid  
(not included)

S3 E-Liquid  
(not included)

S3 Loose Leaf  
(not included)

# Vapour2™ PRO SERIES 3X

VMR CZ, S.R.O.

Konevova 2660/141, Praha 3 Žižkov 130 00 CZ  
Designed by VMR Products LLC in the USA.  
Assembled in China. ©VMR Products LLC  
vapour2.eu | vapour2.co.uk | vapour2.cz

+420 222 264 473 | +44 (0)1733 555 555 | +420 800 622 222

# Vapour2™ PRO SERIES 3X

## USER MANUAL



## Initiating Your Device

1. Remove Series 3X components from their packaging and charge your device, using the included USB Charger.
2. Unscrew the mouthpiece of your cartridge and fill the chamber.
3. Align the small circle on the side of the cartridge (below the mouthpiece) with the notch on your device and slide the cartridge into the cartridge chamber.



4. Unlock your device for use by pressing the Activation Button three times. The LED Perimeter will flash white. Locking your device is the same three clicks, with the LED Perimeter flashing red.
5. Press the Activation Button and take a puff. Discover the satisfaction of Series 3X!

## Get Charged

Series 3X arrives with a partial charge, so make sure you completely charge the unit before your first use. Plug the USB charger into a USB port and connect the magnetic head to the Metal Charge Port on the end of the device. The LEDs surrounding the Activation Button and along the Perimeter will flash, indicating that Series 3X is charging. The LED perimeter will pulse red; turning solid green when Series 3X is fully charged.

Series 3X will need to be recharged when the LED Perimeter begins a set of red double flashes that dim off. But this won't put your experience on pause – Series 3X is designed for use while charging. Connect Series 3X to the USB charger and continue normal use.

## Locking and Unlocking Series 3X


Like your cell phone, Series 3X has a lock feature to prevent accidental activation. Push the Activation Button three times. The LED Perimeter will flash red. This will lock Series 3X and render it unresponsive to accidental input when not in use. To unlock, push the Activation Button three times. The LED Perimeter will flash white, indicating that Series 3X is ready to use.

## Battery Life Indicator

To see the amount of charge remaining in your Series 3X device, simply shake your device a few times. The LED Perimeter will glow, indicating how much charge is remaining. The LED Perimeter lights will correspond with five battery levels.

Note: This function will shut off following ten minutes of inactivity. To reactivate the battery life indicator, press the Activation Button once.

## BATTERY LEVELS



## Stealth Mode

Your Series 3X device has a stealth mode feature that will dim all LED lights.

To activate stealth mode, press the Activation Button nine times. To exit stealth mode, press the Activation Button nine times, or lock and then unlock your device.

## Series 3X Compatible Cartridges

Series 3X is able to vaporize two different types of mediums: e-liquid and loose leaf. V2 Pro offers several types of Series 3 compatible cartridges, with each specially designed for use with a specific medium. The intelligent mechanics of Series 3X allow it to automatically recognize each type of cartridge and perform accordingly. Series 3x is also backwards compatible with all Series 3 cartridges.

## Changing the Atomizer in Your Series 3X Cartridge

To access the atomizer, first unscrew the bottom of the cartridge, and then and then unscrew the atomizer from the bottom of the cartridge. Replace the atomizer with your desired compatible atomizer. There are three interchangeable atomizers available for the Series 3X E-liquid cartridge: 0.9 Ω, 1.2 Ω & 1.5 Ω. If there has already been liquid inside the cartridge, be sure to hold the cartridge upside down to keep any liquid from falling out. Do not attempt to change the atomizer in a cartridge filled with liquid.

## Adjusting Airflow on the Series 3X Cartridge

Just below the mouthpiece of your Series 3X cartridge is a metal ring that rotates to your desired amount of airflow. To adjust the amount of airflow, rotate the ring to your preference.

## ADJUSTING AIRFLOW



## Cartridge Use

### E-Liquid Cartridge

1. Unscrew the mouthpiece from the cartridge and drip e-liquid into the small slot next to the hollow center post.
  - Hold the cartridge at a slight angle when filling it to prevent spills.
  - Do not fill beyond the full line.
  - Do not allow liquid to fall into the center post.
2. Replace the mouthpiece
3. To adjust airflow, twist the air flow ring to your desired setting. (Detailed instructions above. See "Adjusting Airflow")
4. To change the atomizer, unscrew the current one and replace with your desired atomizer. (Detailed instructions above. See "Changing the Atomizer")
5. Insert the cartridge into the Series 3X cartridge chamber.
6. Make sure that Series 3X is unlocked.
7. If desired, set your preferred voltage. (See "Setting the Voltage")
8. Press the Activation Button and begin puffing.
  - If the Activation Button is pressed for ten seconds or longer while the E-liquid cartridge is in use, the LED lights will flash white five times before Series 3X automatically cuts off. This eliminates the potential for accidental activation.

## Setting the Voltage on Series 3X:

Series 3X has three different voltage settings for E-liquid cartridges: 1.8 V, 2.5 V, and 3.3 V. Choosing a higher voltage setting will produce more vapor. To select the voltage, press the Activation Button twice. Series 3X will enter voltage setting mode. While Series 3X is in voltage setting mode, the Manual Control LEDs (on the back of unit) will cycle, indicating three different voltage settings. To make your selection, press the Activation Button once when the glowing LEDs correspond with your desired voltage.

## SETTING VOLTAGE



## Loose Leaf Cartridge

1. Remove the mouthpiece from the cartridge.
2. Add loose leaf to the chamber.
  - a. For best results, use loose leaf that is ground or shredded.
  - b. Be sure not to pack tightly or above the white ceramic ring.
3. Replace the mouthpiece and insert the cartridge into the cartridge chamber.
4. Make sure that Series 3X is unlocked.
5. If desired, set your preferred temperature. (Detailed instructions above. See "Setting the Voltage on Series 3X")
6. Press and hold the Activation Button until the LED Perimeter turns red, indicating heating has started. Once heating has started you can let go of the button.
7. As Series 3X warms to optimal temperature, the LED Perimeter will change from red to green. When the LED Perimeter is green, Series 3X has reached the ideal temperature to vaporize loose leaf. Puff freely without pressing the Activation Button.
8. Press and hold the activation button to turn off the heating, or heating will automatically cut off two minutes after the LED Perimeter has turned green. The LED Perimeter will flash green 5 seconds before cut off.

## Loose Leaf Cartridge Maintenance

Your Loose Leaf cartridge comes with the tools needed to perform regular maintenance. Use the pick to remove particles of used loose leaf, and the brush to sweep away smaller debris left inside the chamber.

## QUICK CLICK GUIDE

